# miso

## 4 Seats

### **STANDARD FEATURES**

#### **BODY PANELS**

ABS 747 injection molded PP panels infused with automotive grade UV resistant gloss finish colour.

#### BATTERIES

8V deep cycle heavy duty lead acid batteries, 6-7 short charge cycle.

#### MOTOR

Premium quality AC 48V 4kw high efficiency.

#### CHARGER

High frequency intelligent charger. Input single phase 115/230 VAC 50/60 Hz & Output DC 48V 18A fully automatic.

#### STEERING

Self-adjusting permanently lubricated rack & pinion steering with sealed tie-rod ends.

#### **SUSPENSION**

Automotive style fully independent with helical springs over hydraulic strauts, cast front hubs and permanently lubricated sealed bearings.

#### TRANS-AXLE

Direct coupled, splineless with high ratio precision helical gears @ 10.5:1 drive ratio. Low noise, minimal wear, low maintenance and long life.

#### CONTROLLER

Toyota 350 Amps programmable.

#### BRAKES

Mechanical brake with foot brake.

#### CHASSIS

Seamless ladder style high tensile tubular steel with anti-corrosive fully immersion phosphate treatment, electro-deposition epoxy base coating and electrostatically applied laser painted top coast for maximum durability.

#### WARRANTY

Two years or 2,000 hours against manufacture defective parts.



Vehicles may be shown with optional equipment. Specification, standard equipment, accessories, and modifications are subject to change without notice.

#### ENJOY THE FOLLOWING OPTIONS:

ŧ	Windshield	+	Heavy duty front and rear bumper
ŧ	Deluxe light package	+	Regenerative braking system
+	Turning signal	+	Front left & right gloves on dashboard
4	Built in charger	+	Cup holder
+	Horn	+	Body colour metallic finish
4	Reverse Alarm	+	Sun top same as body color
ŧ	Battery discharge indicator	ŧ	Sports rim 10"
4	Speedometer	+	Heavy duty tire 10"
4	Odometer	4	Suntop

#### SPECIFICATIONS

Length (mm)	3560
Width (mm)	1200
Height (mm)	1880
Ground Clearance – min. (mm)	114
Track (mm) Front tire : Rear tire	900/1000
Range (km)	80
Forward Speed (km/hr)	40
Braking Distance (meters)	4
Turning Radius (meters)	4.1
Climb Capacity	20/30
Net Weight W/Batteries (kg)	565
Load Capacity (kg)	500
Passenger Capacity	4

FIRST INTERNATIONAL SPECIALIZED VEHICLES TRADING Website: www.firstinternational.ae | Email: sales@firstinternational.ae P.O. BOX 18176, DUBAI, UAE TEL: 971 4 881 9960 | 800-GOLFCARS