# 4 Seats

# STANDARD FEATURES

# **BODY PANELS**

ABS 747 Injection molded P.P. panels infused with automotive grade U.V. resistant gloss colour finish.

# **BATTERIES**

8V deep cycle heavy duty lead acid batteries, 6-7 short charge cycle.

## **MOTOR**

Premium quality AC 48V 4kw high efficiency

#### **CHARGER**

DC 48V 18A fully automatic high frequency intelligent charger

## **STEERING**

Self-adjusting, permanently, lubricated rack & pinion steering with sealed tierod ends.

# **SUSPENSION**

Automotive style fully independent with helical springs over hydraulic strauts, cast aluminum front hubs and permanently lubricated sealed bearings.

# **TRANS-AXLE**

Direct coupled, splineless with high ratio precision helical gears @ 10.5:1 drive ratio. Low noise, minimal wear, low maintenance and long life.

## **CONTROLLER**

Toyota 350 amps Programmable

## **CHASSIS**

Seamless ladder style high tensile tubular steel with anti-corrosive full immersion phosphate treatment, electro-deposition epoxy base coating and electrostatically applied laser painted topcoat for maximum durability.

# **BRAKES**

Mechanical brake with foot brake

## **WARRANTY**

Two years or 2,000 hours against manufacture defective parts.



Vehicles may be shown with optional equipment. Specifications, standard equipment, accessories, and modifications are subject to change without notice.

## **ENJOY THE FOLLOWING OPTIONS:**

<b>↓</b> Straight Windshield	♣ Regenerative braking system
Suntop	♣ Front left & right gloves on dashboard
♣ Deluxe LED light package (Headlight, Brake & Taillight)	♣ Front Basket
<b>↓</b> Turning Signal	<b>↓</b> Cup Holder
<b>↓</b> Built in Charger	♣ Heavy Duty Front and Rear Bumper
<b>↓</b> Horn	<b>↓</b> Speedometer
<b>↓</b> Reverse Alarm	<b>↓</b> Odometer
<b>♣</b> Battery Discharge Indicator	♣ Heavy Duty Wheel and Tire

# **SPECIFICATIONS**

Length (mm)	3120
Width (mm)	1200
Height (mm)	1920
Ground Clearance (mm)	114
Wheelbase (mm)	930/1010
Range (km)	80-100
Forward Speed (km/hr)	40
Braking Distance (meter)	≤ 2.5
Turning Radius (meter)	4.2
Climb Capability (Full Load-Safe/Max%)	25
Tires	8"
Rec. Air Pressure (PSI)	34
Net Weight – No Batteries (kg)	380
Load Capacity (kg)	540