- 11

# Cargo Van

# **STANDARD FEATURES**

#### **BODY PANELS**

ABS 747 Injection molded P.P. panels infused with automotive grade U.V resistant gloss colour finish.

### BATTERIES

8V deep cycle heavy duty lead acid batteries, 6-7 short charge cycle.

**MOTOR** Premium quality AC 48V 5 kw high efficiency

#### CHARGER

High frequency intelligent charger. Input single phase 115/230 VAC 50/60 Hz & Output DC 72V 25A fully automatic.

# STEERING

Self-adjusting, permanently, lubricated rack & pinion steering with sealed tierod ends.

#### **SUSPENSION**

Automotive style fully independent with helical springs over hydraulic strauts, cast aluminum front hubs and permanently lubricated sealed bearings.

## **TRANS-AXLE**

Direct coupled, splineless with high ratio precision helical gears @ 12.31:1 drive ratio. Low noise, minimal wear, low maintenance and long life.

#### CONTROLLER

Toyota 350 amps Programmable

## CHASSIS

Seamless ladder style high tensile tubular steel with anti-corrosive full immersion phosphate treatment, electro-deposition epoxy base coating and electrostatically applied laser painted topcoat for maximum durability.

**REAR CARGO BOX DIMENSION** 2598 x 1426 x 1256mm. Capacity 1,000kg

**BRAKES** Mechanical brake with foot brake

**WARRANTY** Two years or 2,000 hours against manufacture defective parts.



Vehicles may be shown with optional equipment. Specifications, standard equipment, accessories, and modifications are subject to change without notice.

# **ENJOY THE FOLLOWING OPTIONS:**

4 Windshield	Regenerative braking system
4 Wiper	4 Front left & right gloves on dashboard
Deluxe light package)	Sports rim 10"
4 Turning Signal	Cup Holder
+ Built in Charger	Heavy Duty Front and Rear Bumper
<b>↓</b> Horn	4 Speedometer
<b>↓</b> Reverse Alarm	4 Odometer
Battery Discharge Indicator	Heavy Duty Tire 10"

## **SPECIFICATIONS**

Length (mm)	3958
Width (mm)	1496
Height (mm)	1985
Ground Clearance (mm)	180
Wheelbase (mm)	1940
Range (km)	80-100
Forward Speed (km/hr)	30 (Programmable)
Braking Distance (meter)	4
Turning Radius (meter)	5.2
Climb Capability	15%
Net Weight with Batteries (kg)	1250
Load Capacity (kg)	1500
Passenger Capacity	2

FIRST INTERNATIONAL SPECIALIZED VEHICLES TRADING Website: www.firstinternational.ae | Email: sales@firstinternational.ae P.O. BOX 18176, DUBAI, UAE TEL: 971 4 881 9960 | 800-GOLFCARS