

## STANDARD FEATURES

### BODY PANELS

ABS 747 injection molded PP panels infused with automotive grade UV resistant gloss colour finish.

### BATTERIES

8V deep cycle heavy duty lead acid batteries, 6-7 short charge cycle.

### MOTOR

Premium quality AC 48V 4kw high efficiency.

### CHARGER

High frequency intelligent charger.  
Input single phase 115/230 VAC 50/60 Hz & Output DC 48V 18A fully automatic.

### STEERING

Self-adjusting permanently lubricated rack & pinion steering with sealed tie-rod ends.

### SUSPENSION

Automotive style fully independent with helical springs over hydraulic struts, cast front hubs and permanently lubricated sealed bearings.

### TRANS-AXLE

Direct coupled, splines with high ratio precision helical gears @ 10.5:1 drive ratio. Low noise, minimal wear, low maintenance and long life.

### CONTROLLER

Toyota 350 Amps programmable.

### BRAKES

Mechanical brake with foot park brake

### HOUSEKEEPING LOAD SPACE

L- 1650mm x W- 1100mm x H- 1020mm  
Capacity 1000kg.

### CHASSIS

Seamless ladder style high tensile tubular steel with anti-corrosive fully immersion phosphate treatment, electro-deposition epoxy base coating and electrostatically applied laser painted top coat for maximum durability.

### WARRANTY

Two years or 2,000 hours against manufacture defective parts.



Vehicles may be shown with optional equipment. Specification, standard equipment, accessories, and modifications are subject to change without notice.

## ENJOY THE FOLLOWING OPTIONS:

✦ Windshield	✦ Heavy duty front and rear bumper
✦ Deluxe light package	✦ Regenerative braking system
✦ Turning signal	✦ Front left & right gloves on dashboard
✦ Built in charger	✦ Cup holder
✦ Horn	✦ Suntop
✦ Reverse Alarm	✦ Sun top same as body color
✦ Battery discharge indicator	✦ Sports rim 10"
✦ Speedometer	✦ Heavy duty tire 10"
✦ Odometer	✦ Body color metallic finish

## SPECIFICATIONS

Length (mm)	3650
Width (mm)	1120
Height (mm)	1850
Ground Clearance – min. (mm)	114
Track (mm)	900/1000
Range (km)	80
Forward Speed (km/hr)	40
Braking Distance (meters)	6
Turning Radius (meters)	4
Climb Capacity	18%
Net Weight W/Batteries (kg)	580
Load Capacity (kg)	500
Passenger Capacity	2

## FIRST INTERNATIONAL SPECIALIZED VEHICLES TRADING

Website: [www.firstinternational.ae](http://www.firstinternational.ae) | Email: [sales@firstinternational.ae](mailto:sales@firstinternational.ae)

P.O. BOX 18176, DUBAI, UAE

TEL: 971 4 881 9960 | 800-GOLFCARS