

E1-Car

Shuttle Bus

STANDARD FEATURE AND SPECIFICATIONS

BODY	“PP” Alloy automatic industrial special plastic
BATTERY	8 units, 6V T-105 (American Trojan)
MOTOR	DC 48V 4KW High Efficiency
CHARGER	48V 25A
CONTROLLER	USA Curtis 1268
LOAD CAPACITY	8 persons
FORWARD SPEED	32 km/h
TURNING RADIUS	5m
GROUND CLEARANCE	180mm
MILEAGE	80-100km (on flat road)
TIRES	8/10/12
DIMENSION (LWH)	4145 x 1480 x 1900mm



8 Seater

BODY	“PP” Alloy automatic industrial special plastic
BATTERY	8 units, 6V T-105 (American Trojan)
MOTOR	DC 48V 4KW High Efficiency
CHARGER	48V 25A
CONTROLLER	USA Curtis 1268
LOAD CAPACITY	11 persons
FORWARD SPEED	32 km/h
TURNING RADIUS	5m
GROUND CLEARANCE	180mm
MILEAGE	80-100km (on flat road)
TIRES	8/10/12
DIMENSION (LWH)	4500 x 1480 x 1900mm



11 Seater

BODY	“PP” Alloy automatic industrial special plastic
BATTERY	9 units, 8V T-105 (American Trojan)
MOTOR	AC 72V 7.5KW High Efficiency
CHARGER	72V 30A
CONTROLLER	USA Curtis 1236
LOAD CAPACITY	14 persons
FORWARD SPEED	20-28 km/h
TURNING RADIUS	5.3m
GROUND CLEARANCE	230mm
MILEAGE	100-120km (on flat road)
TIRES	8/10/12
DIMENSION (LWH)	4970 x 1490 x 2020mm



14 Seater

Vehicles may be shown with optional equipment. Specifications, standard equipment, accessories, and modifications are subject to change without notice.

FIRST INTERNATIONAL SPECIALIZED VEHICLES TRADING

Website: www.firstinternational.ae | Email: sales@firstinternational.ae

P.O. BOX 18176, DUBAI, UAE

TEL: 971 4 881 9960 | 800-GOLFCARS